





- ✓
- ✓
- ✓
- ✓
- ✓
- ✓
- ✓



SRM900-C:

5G-NR: N1/N28/N41/N78/N79
LTE-FDD: B1/B3/B5/B8
LTE-TDD: B34/B38/B39/B40/B41

SRM900-E:

5G-NR: N1/N3/N20/N28/N78
LTE-FDD: B1/B3/B5/B7/B8/B20
LTE-TDD: B38/B40/B41

SRM900-J:

5G-NR: N1/N3/N77/N78/N79
LTE-FDD: B1/B3/B8/B9/B19/B26/B28
LTE-TDD: B41

SNM930:

Wi-Fi & BT

TBD

&
VoLTE

24-bit/192kHz

SRVCC/CSFB

2520x1080@60fps + QHD60 via DisplayPort
One 4-lane DSI, D-PHY 1.2, C-PHY 1.0
DisplayPort support over USB Type-C

I2C

4 x 4-lane CSI
3 x ISP 14 bit + 1 x lite ISP: 16 + 16 + 16 MP
32M

1

USB

USB 3.0*1

QC4.0

USB 3.0/2.0

Display Port

USB OTG

*4 GNSS

*1 Wi-Fi&BT

*2

I2C 5

(U)SIM 2 1.8V/2.95V

UART 3

SD 1 (4Mbps)

PWRKEY 1.8V SD 3.0, 4-bit SDIO

SPI 2 1 UART 1 I2S

ADC 2

GPIO 19

Flashlight 1

LED 2

4

WLAN 2.4G/5G, 2x2 MU MIMO, 802.11 a/b/g/n/ac ax ready
BT2.1+EDR/3.0/4.1 LE/5.x BLE

GNSS GPS/GLONASS/BeiDou, L1+L5 GNSS

Modem

3GPP Rel.15 5G NR

sub-6GHz 5G NR

256 QAM uplink/downlink in sub-6GHz

Rel.15 LTE multi-mode modem

Quick Charge 4.0

USB

Android 11

64GB UFS+4GB LPDDR4x

128GB UFS+6GB LPDDR4x

128GB UFS+8GB LPDDR4x

-30°C~+75°C

-40°C ~ +90°C

3.5V~4.35V

3.8V

47.0mm × 48.0mm × 3.0mm

LGA

13.0g

CCC

*