



MeiG-SRM928

5G

3GPP Rel-15



SRM928	UNISOC 7885	1*A76@2.7GHz+3*A76@2.3GHz+4*A55@2.1GHz
6nm	ARM Mali™-G57 GPU	4K@ 60 fps
H.264/H.265	20M+20M+2M+2M	
SRM928	5G	AI POS PDA
ARM		

✓	DL 4 × 4 MIMO SA/NSA			
✓	NPU 8 TOPS AI	UNISOC 7885	ARM Mali™-G57	Android 13
✓	QHD+ (3360 × 1440) @60fps			
✓				
✓	4K@ 60 fps	DL 4x4 MIMO	LGA	8 Tops
✓	Android13	Android		
✓	:PCIE/ USB / GPIO / SPI / UART / ...			

MeiG-SRM928

5G

42.5mm

5G CPE Module

SRM928XX-320X

IMEI:XXXXXXXXXXXXXXX

S/N:MeiGXXXXXXXXXXXXXXX

MeiGLink

5G

42.5mm

5G CPE Module

SRM928XX-320X

IMEI:XXXXXXXXXXXXXXX

S/N:MeiGXXXXXXXXXXXXXXX

MeiGLink

5G

42.5mm

5G CPE Module

SRM928XX-320X

IMEI:XXXXXXXXXXXXXXX

S/N:MeiGXXXXXXXXXXXXXXX

MeiGLink

GSM: B3/B8

- | | | | | |
|-------------------------|-------------------|-----|---|----------|
| • I2C: x9 | 8 | I2C | 1 | I2C |
| • I2S: x4 | 2 | I2S | 2 | I2S |
| • (U)SIM: x2 (1.8V/3.0V | | | | |
| • UART: x6 | | | | |
| • SD : x1 (SD 3.0, | | | | |
| • SPI: x2 | 1 | SPI | 1 | SPI |
| • ADC: x3 | | | | |
| • PCIe: | 1-lane PCIe Gen 3 | | | 7.8 Gbps |

- Decode: 4K@60fps 10 bit H.264/H.265/VP9
- Encode: 4K@60fps H.264/H.265

- WLAN: 2.4/5G, 802.11a/b/g/n/ac
- : BT5.0
- GNSS: GPS/GLONASS/Galileo/Beidou, L1
- USB

- 2 4-lane MIPI-DSI
- QHD + (3360 × 1440) @ 60 fps FHD + (2520 × 1080) @ 120 fps

OS: Android 13

- 4 4-lane MIPI CSI
- 64 MP @ 30 fps ZSL

64 GB UFS + 4 GB LPDDR4X
128 GB UFS + 4 GB LPDDR4X
128 GB UFS + 6 GB LPDDR4X
128 GB UFS + 8 GB LPDDR4X
256 GB UFS + 8 GB LPDDR4X

- $$\begin{array}{ccc} \bullet & & \vdots \\ \bullet & & \vdots 4 \end{array}$$

: -35°C ~ +75°C
: -40°C ~ +90°C
: 3.55V~4.4V : 4.0V

- 1*USB 3.0

: 56.5mm×42.5mm×2.95mm
A
.5g

*4, GNSS *1, Wi-Fi&BT *2

CCC*

*

Tel 021-54278676 Fax 021-54278679 Web <http://www.meigsmart.com>

2337 G 5

Add 5th floor,building G,no.2337 gudai road(weijing center),minhang District,Shanghai,China.

002881

MeiG Smart Technology Co., Ltd Stock Code 002881.SZ